



Professional 3D LiDAR Scanner **SHARE3DCAM C10 Series**

Complex Environments , Precise Reconstruction

Product Highlights



Point rate up to
640,000 pts/s



Ultra-long measurement
range up to 300 m



1-inch mechanical-shutter
wide-angle camera



Visual laser-based
GCP acquisition



RTK/PPK high-precision
positioning



Dual hot-swappable batteries

Product Specifications

Product	 SHARE3DCAM C10-16	 SHARE3DCAM C10-32	 SHARE3DCAM C10-32 PRO
LiDAR Channel	16	32	32
Point Cloud Number	320,000 points/s	640,000 points/s	640,000 points/s
Scanning Range	0.5 ~ 120 m	0.5 ~ 120 m	0.5 ~ 300 m
Number of Camera	2		4
Sensor Size	1-inch (13.13 × 8.76 mm); Pixel Size: 2.4 μm		
Effective Pixels	16 MP		
Dimensions	386.8mm*152.7mm*174.4mm		
Weight	2438g		2328g
Wi-Fi	Wi-Fi 6, supports 2.4 GHz / 5 GHz, 20m		
Panoramic Image Stitching	Not supported		Supported
Storage Capacity	1TB SSD		
RTK Accuracy	Horizontal: 0.8 cm + 1 ppm; Vertical: 1.5 cm + 1 ppm		
IMU frequency	1000HZ		
Load-Bearing System	Standard Multi-Functional Ergonomic Load-Bearing System		
Battery Capacity	49.436wh (3400mAh) * 2pcs		
Runtime	Approx. 180 minutes		
Point Cloud Thickness	≤ 5 mm		
Relative Accuracy	≤ 1 cm		
Absolute Accuracy	≤ 5 cm		

SHARE 3DCAM

WWW.SHARE3DCAM.COM

LinkedIn



YouTube



Instagram



Facebook

